



## HOUSTON FLAT HOSE RED

### GENERAL PURPOSE PVC WATER DISCHARGE HEAVY DUTY



#### Applications

- Equipment rental
- Construction
- Agricultural
- General open water discharge

#### Construction

- Features a balanced polyester yarn spiral wrap, longitudinal strength member and homogeneous PVC tube and cover to prevent separation.

#### Features & Benefits

- Smooth Tube - Provides low friction loss.
  - EEZ - An easy to handle lightweight hose for general purpose applications.
  - Ultraviolet inhibitors - Reduces aging and weather checking
  - Storage - All coils have PVC cores for easier dispensing.
- Hose coils flat for easy storage.

#### Nominal Specifications

| CODE       | SIZE<br>(in.) | SIZE<br>(mm.) | HOSE ID<br>(in.) | HOSE ID<br>(mm.) | APPROXIMATE<br>WALL THICKNESS<br>(in.) | WORKING<br>PRESSURE<br>(PSI) | ROLL<br>LENGTH<br>(ft.) | APPROXIMATE<br>WEIGHT<br>(lbs./coil) |
|------------|---------------|---------------|------------------|------------------|----------------------------------------|------------------------------|-------------------------|--------------------------------------|
| PIDWLR-025 | 1             | 25.4          | 1.024            | 26.0             | .051                                   | 150                          | 100                     | 30.0                                 |
| PIDWLR-032 | 1 1/4         | 31.8          | 1.299            | 33.0             | .051                                   | 150                          | 100                     | 35.0                                 |
| PIDWLR-038 | 1 1/2         | 38.1          | 1.614            | 41.0             | .045                                   | 150                          | 100                     | 42.0                                 |
| PIDWLR-050 | 2             | 50.8          | 2.087            | 53.0             | .048                                   | 150                          | 100                     | 49.0/8.0                             |
| PIDWLR-076 | 3             | 76.2          | 3.071            | 78.0             | .055                                   | 150                          | 100                     | 90.0/15.0                            |
| PIDWLR-101 | 4             | 101.6         | 4.094            | 104.0            | .056                                   | 150                          | 100                     | 131.0                                |
| PIDWLR-152 | 6             | 152.4         | 6.102            | 155.0            | .061                                   | 120                          | 100                     | 209.0                                |
| PIDWLR-203 | 8             | 203.2         | 8.169            | 208.0            | .073                                   | 90                           | 100                     | 312.0                                |